

- **SpamAssassin**

SpamAssassin is the leading open source spam scanner. We'll be installing SpamAssassin via CPAN below.

**NOTE:** Debian users should have installed the SpamAssassin prerequisites during 'Debian Notes' earlier. RPM distributions may want to use 'yum install spamassassin' instead of CPAN below, so that you get all the dependencies. If the RPM of SpamAssassin is out of date, you could then simply do 'yum uninstall spamassassin', and follow the CPAN installation below, as you'll have the dependencies.

Info: <http://www.spamassassin.org>

Install:

```
cd /root
perl -MCPAN -e shell
o conf prerequisites_policy ask
install Mail::SpamAssassin
quit

# run spamd under daemontools
mkdir -p /var/qmail/supervise/spamd/log
mkdir -p /var/log/spamd
chown qmail /var/log/spamd
cp /var/src/toaster-scripts-0.9.0/spamd.run
/var/qmail/supervise/spamd/run
cp /var/src/toaster-scripts-0.9.0/spamd.log.run
/var/qmail/supervise/spamd/log/run
chmod 755 /var/qmail/supervise/spamd/run
chmod 755 /var/qmail/supervise/spamd/log/run
cp /var/src/toaster-scripts-0.9.0/local.cf
/etc/mail/spamassassin/local.cf
mkdir /etc/mail/spamassassin/.spamassassin/
chown vpopmail /etc/mail/spamassassin/.spamassassin/
ln -s /var/qmail/supervise/spamd /service
```